

# RA-2000 / RA-2000GRAY

## Remote Annunciator

The RA-2000 or RA-2000GRAY remote annunciators can be used to operate and program the Honeywell Farenhyt Series FACP's. The RA-2000 has a large 160 character, 4 x 40 display and four programmable buttons. These features provide more options for set-up and operation when compared to similar remote annunciators.

The RA-2000 comes in a locked, key controlled cabinet - combining security with easy access. It does not require a code or firefighter's key to silence or reset a panel, and also has convenient separate scroll buttons for alarm, supervisory and trouble conditions. The remote annunciator communicates with the main fire alarm control panel through an RS-485 connection.

The RA-2000 can be surface or flush mounted and is also available in gray color as RA-2000GRAY.



**RA-2000**

### COMPATIBILITY


The RA-2000 or RA-2000GRAY are compatible with the following Honeywell Farenhyt Series FACP's:

- IFP-2000/ECS
- IFP-2100/ECS
- IFP-75
- IFP-300/ECS
- RPS-2000
- RFP-2100
- ECS-LOC

## FEATURES & BENEFITS

- Four line LCD display with 40 characters per line
- Tactile/audible feedback when key is pressed on annunciator
- RS-485 SBUS interface to panel
- Initiate and end fire drills with a single key press
- Can be flush or surface mounted. Trim ring (P/N RA-100TR or RA-2000GRAYTR) available for surface mounting
- Multi-panel displays can display the status and event history of all the panels they are assigned in a network
- Multi-panel annunciators will sound the highest priority tone from the panel it is assigned to
- View current status by alarms, supervisory, or troubles
- On-board piezo sounder audibly indicates alarms, troubles, and supervisory
- Five Status LEDs for: alarms, supervisory, trouble, silence and AC power indications
- Four programmable function keys
- Available in red or gray color
- Wiring lengths up to 6000 ft. from the control panel
- UL listed, complies with NFPA 72

# RA-2000 Technical Specifications



## RA-2000 FEATURES

### PHYSICAL

#### Flush Mount

**Outside wall:** 12.25"W x 11.5"H x 7/8"D (31.1W x 29.2H x 2.2D cm)

**Inside wall:** 9-3/8"W x 8-3/8"H x 2"D (23.8W x 21.3H x 5.1D cm)

**Surface Mount:** (Including Trim Ring) 12.25"W x 11.5"H x 3"D (31.1W x 29.2H x 2.2D cm)

### ENVIRONMENTAL

**Operating Temperature:** 32°F to 120°F (0°C to 49°C)

**Humidity:** 0 to 93% relative humidity (non-condensing)

### ELECTRICAL

**Operating Voltage:** 24VDC

**Standby Current:** 25mA

**Alarm Current:** 50mA

### ORDERING INFORMATION

**RA-2000:** Remote Annunciator. Red

**RA-2000GRAY:** Remote Annunciator. Gray

### OPTIONAL ACCESSORIES

**RA-100TR:** Red surface mount trim ring

**RA-2000GRAYTR:** Gray surface mount trim ring

### AGENCY LISTINGS AND APPROVALS

UL listed

CSFM approved

NFPA 72

FM approved

FDNY COA#: 6162

For a complete listing of all compliance approvals and certifications, please visit [www.farenhyt.com](http://www.farenhyt.com).

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation.

Honeywell® is a registered trademark of and Farenhyt™ is a trademark of Honeywell International, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For Technical Support, Please call 800-446-6444.

### For more information

Learn more about Honeywell's Farenhyt Series and other products available by visiting [www.farenhyt.com](http://www.farenhyt.com)

### Honeywell Security & Fire

12 Clintonville Road  
Northford, CT 06472  
800-328-0103

350401 | G | 11/17  
© 2017 Honeywell International Inc.

**Honeywell**