



Network Node

Overview

The Network Node intelligent field panel handles distributed processing for Elements Cloud access control systems. Access control and events from connected devices are aggregated to the Elements web interface for centralized system management and control.

The Network Node panel supports up to seven modular LenelS2 application blades for access control, inputs, and outputs. Any LenelS2 application blades can be combined to fit deployment requirements. Blades are automatically addressed without jumpers or switches. External devices such as 12VDC card readers can be powered from the LenelS2 access control application blade without the need for external power supplies.




Key Features

Access Control

- **Blade Support:** Houses up to seven LenelS2 application blades for access control, inputs, and outputs
- **Readers:** Supports up to fourteen doors or other access points
- **Input Assignment:** Enables assignment of up to 56 supervised inputs
- **Output Assignment:** Enables assignment of up to 56 form C output relays

System

- **LenelS2 System Node:** Handles distributed access control and event monitoring
- **Solid State Design:** Extends product lifecycle, lowering total cost of ownership
- **Offline Availability:** Maintains access control capabilities even when connectivity to the Elements system is lost
- **Intuitive Configuration:** Utilizes embedded web interface for initial setup



Specifications – Network Node

Access Control		Hardware (continued)	
Network Node Blade	M1-3200	Operating Temperature	32° – 95°F (0° – 35°C)
Application Blades / SIOs	7	Storage Temperature	-4° – 158°F (-20° – 70°C)
Readers	14	Input Power	100 - 240 VAC, 50/60 Hz, 2.3A
Supervised Inputs	56	Reader Output Power	12VDC, 250 mA/reader
Relay Outputs	56	BTU Maximum	184 per hour
Credential Storage	150,000	Commissioning	Web configuration utility
Buffered Transactions	800,000	Regulatory Approvals	UL, CE, FCC, RoHS
Hardware		Part Numbers	
Storage	2GB Flash	S2-NN-E-WM	Supports up to 7 LenelS2 application blades, wall mount
Processor	TI AM3352 ARM	S2-NN-E-RM	Supports up to 7 LenelS2 application blades, rack mount
Memory (RAM)	512MB SDRAM	S2-ACM	Dual Reader Interface Blade
Operating System	Linux	S2-INP	Input Control Blade
Ethernet Ports	1	S2-OUTP	Output Control Blade
MTBF	297,000 hrs		
Chassis	Wall mount or standard 4U rack mount		
Dimensions (H, W, D)	Wall Mount: 17.0in x 15.0in x 6.75in (432mm x 381mm x 172mm) Rack Mount: 7.0in x 19.0in x 15.0in (178mm x 483mm x 381mm)		
Weight	Wall Mount: 18 lbs (8.6 kg) Rack Mount: 17 lbs (7.7 kg)		



For more information, please visit lenels2.com.

Specifications subject to change without notice.

© 2024 Honeywell International Inc. All Rights Reserved. All trademarks and service marks referred herein are property of their respective owners.